

P/N	Description	Bandwidth
R43SF	M.2 NVMe to PCIe x16, connector turn 180° splint vertical extension cables	PCIe 3.0 x4 (32G/bps)
R43SR	M.2 NVMe to PCIe x16, connector turn 270° inverted reverse extension cables	PCIe 3.0 x4 (32G/bps)
R43SL	M.2 NVMe to PCIe x16, connector turn 90° extension cable	PCIe 3.0 x4 (32G/bps)
R43MF	M.2 NVMe to PCIe x16, cable turn right, connector turn 180° extension cable	PCIe 3.0 x4 (32G/bps)
R43ML	M.2 NVMe to PCIe x16, cable turn right, connector turn 270° extension cable	PCIe 3.0 x4 (32G/bps)
R43MR	M.2 NVMe to PCIe x16, cable turn right, connector turn 90° extension cable	PCIe 3.0 x4 (32G/bps)
R43UF	M.2 NVMe to PCIe x16, cable turn left, connector turn 180° extension cable	PCIe 3.0 x4 (32G/bps)
R43UL	M.2 NVMe to PCIe x16, cable turn left, connector turn 270° extension cable	PCIe 3.0 x4 (32G/bps)
R43UR	M.2 NVMe to PCIe x16, cable turn left, connector turn 90° extension cable	PCIe 3.0 x4 (32G/bps)